



UT-6405GCA-POE是5口全千兆非网管型POE以太网交换机,5路千兆以太网端口(其中1~4口支持POE以太网供电),可以为IEEE 802.3af/at设备(PD)供电,消除了额外的布线需求,提供直流输入正反接保护防止烧坏仪器,外观设计精巧,同时支持工业标准的导轨式安装和墙式安装,所以它非常容易安装应用在任何工业网络上。该产品提供3种工作模式:延长、标准和VLAN模式,提供POE看门狗功能和POE功率限制功能,专门解决工程中出现的设备死机现象,自动重启死机设备。

1、导轨
2、挂耳
3、电源端子
4、接地螺丝
5、拨码开关


6、电源指示灯
7、10/100/1000Base-T网络接口
8、网络指示灯
9、POE接口指示灯

Technical drawing of the 125x90x30 mm device, showing front, top, and side views with dimensions.

- Front View (Top):** Shows the front panel with a central display area, a small circular indicator on the left, and a small circular indicator on the right. The dimensions are 125.00 mm (width) and 90.00 mm (height).
- Top View (Left):** Shows the top of the device with a small circular indicator on the left and a small circular indicator on the right. The dimensions are 125.00 mm (width) and 90.00 mm (height).
- Side View (Right):** Shows the side of the device with a small circular indicator on the left and a small circular indicator on the right. The dimensions are 125.00 mm (width) and 90.00 mm (height).
- Bottom View (Bottom):** Shows the bottom of the device with a small circular indicator on the left and a small circular indicator on the right. The dimensions are 125.00 mm (width) and 90.00 mm (height).

6.4 电源输入

将电源线插入3芯接线端子的规定位置，把接线端子插入标准电源输入接口，支持供电电压范围48VDC(46-57V)。



七、包装清单

名称	数量（单位）
交换机	1PCS
说明书	1PCS
保修卡	1PCS
产品合格证	1PCS